

Ortac® 400



Marking: Continental 1-1/2" (38.1 mm) Ortac® 250 PSI WP Made in USA

Applications

Ortac® (Oil-Resistant Tube and Cover) is our most popular premium-quality multipurpose hose . Used in the most abusive industrial applications, Ortac® will handle air, oil, water, kerosene and some chemicals. The premium Carbryn™ cover offers the most superior abrasion resistance of air and multipurpose hoses. Non-conductive, minimum electrical resistance greater than 1 megohm per inch of hose length at 1000 volts DC. Note: Ortac® 400 Yellow is USMSHA approved.

Specifications

Construction Tube: Nitrile Synthetic Rubber, ARPM Class A (High Oil Resistance)

Cover: Carbryn™ Synthetic Rubber, ARPM Class A (High Oil Resistance)

Reinforcement: Spiral Synthetic Yarn, 2" is Braided

Coupling: Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes: For special production run minimum requirements, Contact Customer Service

Temperature Range: -20°F to 210°F (-29°C to 99°C)

Order Codes: 569-065 (Yellow) (USMSHA Rated), 569-066 (Red), 536-101 (Red / Black) 2"

Packaging: 3/16" to 3/4" - 500' reels, maximum 3 pieces, 50' increments, 1" - 450' reels, maximum 3 pieces, 50' increments, 1-1/4" - 400' reels, maximum pieces, 50' increments, 1-1/2" - 300' reels, maximum 3 pieces, 50' increments, 2" - 200' cartons, maximum 3 pieces, 50' increments

Technical Data Imperial

Part Number	Color	InnerØ (in)	OuterØ (in)	Weight (lbs/ft)	Working Pressure (PSI)	Length (ft)
20026596	Yellow	1/4	0.61	0.16	400	500
20026598	Yellow	3/8	0.73	0.20	400	500
20026599	Yellow	1/2	0.89	0.26	400	500
20414718	Red	1/2	0.89	0.61	400	328
20026600	Yellow	3/4	1.18	0.41	400	500
20026606	Red	3/4	1.18	0.41	400	500
20026601	Yellow	1	1.50	0.61	400	450
20414716	Red	1	1.50	0.61	400	328

Technical Data Metric

--	--	--	--	--	--	--