

UNITRIX® 60

Marking: Continental ContiTech UNITRIX® 60 DN 13 PN 20 BAR / 290 PSI R < 10*6 Ω Made in Germany

Applications

The multipurpose hose UNITRIX® 60 provides best results when used in the areas of mechanical engineering, farming, forestry, garages, quarries, construction sites as well as shipbuilding and the railway industry. It can be used with compressors, barrel pumps and aggregates. It can also be used in the areas of the mineral oil industry and the chemical and petrochemical industry. UNITRIX® 60 is the right hose for conveying benzene, mineral oil, kerosene, motor oil, compressed air, cold and hot water with or without detergent additives, vegetable oils, animal fats, diluted acids, technical alcohols, pesticides, salt solutions. Ideal for oil cooling lines up to 290 PSI. This hose is manufactured to European standards. Design Factor: 3:1

Specifications

- Construction Tube: Black, non-porous and smooth NBR (Nitrile) Tube ARPM class A (high oil resistance)
- Cover: Black, smooth NBR (Nitrile) cover, resistant to ozone, weather, UV, oil, grease and chemicals ARPM class A (high oil resistance)
- Reinforcement: Synthetic fibers
- Temperature Range: -13°F to 185°F (-25°C to 85°C)

Technical Data Imperial

Part Number	InnerØ (in)	OuterØ (in)	Weight (lbs/ft)	Working Pressure (PSI)	Bend Radius (in.)
20853782	1/2	0.97	0.36	261	5.12
20853781	3/4	1.30	0.60	261	7.48

Technical Data Metric

Part Number	InnerØ (mm)	OuterØ (mm)	Weight (kg/m)	Working Pressure (MPa)	Bend Radius (mm)
20853782	12.70	24.70	0.540	1.8	130
20853781	19.10	33.10	0.890	1.8	190

Got Questions?

Contact our service team. [Contact form \(/Contact-Forms/General-Contact-Form\)](#)