

Insta-Grip™ TC



Marking: Continental ContiTech Insta-Grip™ TC 3/8" 300 PSI WP. Made in USA

Applications

For low-pressure hydraulic and pneumatic systems such as shop air systems, general industrial, maintenance and automotive assembly applications.

Specifications

Construction Tube: Chemivc™ oil- and heat-resistant synthetic rubber, ARPM class A (high oil resistance)

Cover: Black, dyed textile braid, mildew- and oil-resistant

Reinforcement: Braided (1) high-strength synthetic yarn laid at a

Coupling: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes: For special production run minimum requirements, see Appendix D.

Temperature Range: -40°F to 210°F (-40°C to 99°C)

Order Codes: 535-230

Packaging: 500' reels, maximum 4 pieces, 10' minimum length

Technical Data Imperial

Part Number	InnerØ (in)	OuterØ (in)	Weight (lbs/ft)	Working Pressure (PSI)
20022593	1/4	0.50	0.08	300
20022595	5/16	0.56	0.09	300
20022597	3/8	0.64	0.11	300
20022600	1/2	0.75	0.13	300
20022602	5/8	0.91	0.19	300
20022604	3/4	1.03	0.21	300

Technical Data Metric

Part Number	InnerØ (mm)	OuterØ (mm)	Weight (kg/m)	Working Pressure (MPa)
20022593	6.40	12.70	0.12	2.07
20022595	7.90	14.20	0.13	2.07
20022597	9.53	16.30	0.16	2.07
20022600	12.70	19.10	0.19	2.07
20022602	15.90	23.10	0.28	2.07
20022604	19.10	26.20	0.31	2.07