



PLICORD® SAND SUCTION MH Abrasive / Corrosive Hose



APPLICATION: Plicord® Sand Suction hose is for use on the suction end of hydraulic dredges. It provides a flexible connection between dredging lines and pumps.

CONSTRUCTION TUBE: 3/8" Black CHEMITUF(compound)® synthetic rubber for abrasion resistance (static dissipating/static conductive). Also available in 1/2" or 3/4" tube gauge.

COVER: Black SBR(compound)® synthetic rubber (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric with wire helix

TEMPERATURE: -25 °F to 180 °F (-32 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Continental Contitech Style M Sand Suction.

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20371749	4 in 101.60 mm	5.310 in 134.90 mm	20.000 ft	N/A	N/A
20029485	5 in 127.00 mm	6.980 in 177.30 mm	50.000 ft	N/A	N/A
20069811	6 in 152.40 mm	7.540 in 191.50 mm	50.000 ft	N/A	N/A
20207629	6 in 152.40 mm	7.540 in 191.50 mm	25.000 ft	N/A	N/A
20219625	8 in 203.20 mm	9.630 in 244.60 mm	25.000 ft	N/A	N/A
20244539	8 in 203.20 mm	9.690 in 246.00 mm	50.000 ft	62.0 psi 1575.00 MPa	16.930 lb/ft 25.19 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20015160	10 3/4 in 273.70 mm	13.010 in 330.40 mm	10.000 ft	82.0 psi 2083.00 MPa	25.680 lb/ft 38.22 kg/m

videastUS@contitech.us
1-800-235-4632
Contitech.us

