



## SPIRATHANE™ LD MH Abrasive / Corrosive Hose



**APPLICATION:** For dry pneumatic conveying of solid fines where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

**CONSTRUCTION TUBE:** Clear Polyurethane, RMA Class B (Medium Oil Resistance)

**REINFORCEMENT:** High-density rigid white Pliovic® helix

**TEMPERATURE:** 0 °F to 158 °F (-18 °C to 70 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Not branded

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Max. Working Pressure</u>
<a href="#">20013121</a>	1 1/2 in 38.10 mm	1.840 in 46.70 mm	100.000 ft	2.000 in 51.00 mm	30.0 psi 0.21 MPa
<a href="#">20013123</a>	2 in 50.80 mm	2.350 in 59.70 mm	100.000 ft	3.000 in 71.00 mm	25.0 psi 0.17 MPa
<a href="#">20466833</a>	2 in 50.80 mm	2.350 in 59.70 mm	50.000 ft	3.000 in 71.00 mm	25.0 psi 0.17 MPa
<a href="#">20013124</a>	2 1/2 in 63.50 mm	2.890 in 73.40 mm	100.000 ft	4.000 in 89.00 mm	20.0 psi 0.14 MPa
<a href="#">20013125</a>	3 in 76.20 mm	3.450 in 87.60 mm	100.000 ft	4.000 in 102.00 mm	20.0 psi 0.14 MPa
<a href="#">20013127</a>	4 in 101.60 mm	4.530 in 115.10 mm	100.000 ft	7.000 in 178.00 mm	15.0 psi 0.1 MPa
<a href="#">20013126</a>	4 in 101.60 mm	4.530 in 115.10 mm	50.000 ft	7.000 in 178.00 mm	15.0 psi 0.1 MPa

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Max. Working Pressure</u>
<a href="#">20013128</a>	5 in 127.00 mm	5.560 in 141.20 mm	100.000 ft	8.000 in 203.00 mm	10.0 psi 0.07 MPa
<a href="#">20013130</a>	6 in 152.40 mm	6.570 in 166.90 mm	100.000 ft	12.000 in 305.00 mm	10.0 psi 0.07 MPa
<a href="#">20013131</a>	8 in 203.20 mm	8.590 in 218.20 mm	20.000 ft	23.000 in 584.00 mm	6.0 psi 0.04 MPa
<a href="#">20013133</a>	10 in 254.00 mm	10.750 in 273.10 mm	20.000 ft	30.000 in 762.00 mm	5.0 psi 0.03 MPa