



SPIRATHANE™ PT Transfer Hose



APPLICATION: For the transfer of a variety of dry, bulk, and abrasive materials. It is used in applications where static electrical buildup is common. For powders, plastic pellets and granular materials.

CONSTRUCTION TUBE: Polyurethane conforms to FDA standards.

COVER: High molecular weight, clear PVC, corrugated for flexibility.

REINFORCEMENT: High-density, rigid Pliovic® PVC helix with static wire placed between tube and cover.

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
20013682	1 1/2 in 38.10 mm	1.820 in 46.20 mm	100.000 ft	4.000 in 102.00 mm	0.310 lb/ft 0.46 kg/m
20013683	1 3/4 in 44.50 mm	2.150 in 54.60 mm	100.000 ft	5.000 in 127.00 mm	N/A
20013684	2 in 50.80 mm	2.380 in 60.50 mm	100.000 ft	6.000 in 152.00 mm	0.520 lb/ft 0.77 kg/m
20013685	2 1/4 in 57.20 mm	2.770 in 70.40 mm	100.000 ft	7.000 in 165.00 mm	N/A
20013686	2 1/2 in 63.50 mm	3.030 in 77.00 mm	100.000 ft	7.000 in 178.00 mm	0.690 lb/ft 1.03 kg/m
20013687	3 in 76.20 mm	3.630 in 92.20 mm	100.000 ft	8.000 in 203.00 mm	1.15 lb/ft 1.71 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
20013688	4 in 101.60 mm	4.760 in 120.90 mm	100.000 ft	14.000 in 356.00 mm	1.630 lb/ft 2.43 kg/m
20046048	5 in 127.00 mm	5.830 in 148.10 mm	100.000 ft	20.000 in 508.00 mm	2.130 lb/ft 3.17 kg/m
20032298	6 in 152.40 mm	6.300 in 176.00 mm	100.000 ft	N/A	N/A

videastUS@contitech.us
 1-800-235-4632
 Contitech.us

