

# Spiraflex® Aggie PVC



## Product Specifications

### Application

Spiraflex® Aggie PVC is a general-purpose water suction hose for use in industrial, agriculture and construction applications.

### Construction

#### > Tube

Clear Pliovic®

#### > Reinforcement

High-density white rigid Pliovic® helix

#### > Temperature Range

0°F to 158°F (-9°C to 70°C)

### Packaging

100' lengths coiled and poly-wrapped

### Branding

Not branded

### Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

### Order Codes

586-453

## Spiraflex®

SAP #	ID	Nom. OD		Max. WP		Bend Radius		Vacuum HG		Weight			
		in.	mm	in.	mm	in.	mm	in.	mm	lb./ft.	kg/m		
20013491	3/4	19.1	25.4	1.00	25.4	120	0.83	3.0	76	29	737	0.18	0.27
20013493	1	25.4	31.5	1.24	31.5	106	0.73	4.5	114	29	737	0.23	0.34
20013495	1¼	31.8	38.9	1.53	38.9	99	0.68	5.0	127	29	737	0.34	0.51
20013497	1½	38.1	45.2	1.78	45.2	89	0.61	6.0	152	29	737	0.38	0.57
20013500	2	50.8	58.7	2.31	58.7	79	0.54	8.0	203	29	737	0.58	0.86
20013504	2½	63.5	72.4	2.85	72.4	65	0.45	10.0	254	29	737	0.90	1.34
20013507	3	76.2	86.6	3.41	86.6	65	0.45	12.0	305	29	737	1.07	1.59
20013510	4	101.6	113.5	4.47	113.5	55	0.38	16.0	406	29	737	1.69	2.51
20013516	6	152.4	167.6	6.60	167.6	47	0.32	36.0	914	29	737	3.29	4.90

Hose design ratio (burst pressure) 3:1.

**Air & Multipurpose**  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

Cleaning Equipment

**Food**  
Dry Transfer  
Liquid Transfer  
Washdown

Marine

**Material Handling**  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

**Petroleum**  
Aircraft Fueling  
Dispensing  
Dock  
Rig Supply  
Transfer Discharge  
Transfer S&D

Specialty

Steam

Vacuum

**Water**  
Discharge  
Suction & Discharge  
Washdown  
Garden

Welding

Coupling Systems

Equipment

Appendix