

## U-Lok 1030 Heavy Duty Service

### U-Lok 1030

#### Heavy Duty Service Ducting(30 mil Urethane Duct)

This extra heavy duty service duct will stand up to the toughest jobs. Constructed of 30 mil urethane, with an extra wide helix for added scuff resistance and strength. Great flexibility.

#### Applications

Heavy duty abrasion resistance  
Leaf collection  
Material handling, woodworking  
High flexibility. Oil resistant  
U.V. stabilized  
Meets FDA requirements 177.2600

#### Construction

Product code: 3UL1030  
Material: Urethane, 30 mil, mechanical lock corrosion resistant helix  
Diameters: 4" to 14".  
Weight: 6" I.D. = 1.9 lbs/ft  
Colour: Black  
Compression Ratio: 4:1.  
Length 25 ft  
Temperature Range: -20°F (-29°C) to +250°F (121°C)



I.D.	4	5	6	8	10	12
Working Pressure/ PSI	18	18	16	16	14	14
Negative Pressure Inch. H.g	26	21	16	6	5	4.5

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

Due to continuous improvements, technical data subject to change without notice

03.2011

<b>Bromborough, UK</b>	Tel 44.0151.334.0873	Fax 44.0151.334.7145	
<b>Indianapolis, IN</b>	Tel 317.334.1444	Fax 317.334.1535	800.526.6288
<b>Haw River, NC</b>	Tel 336.578.2161	Fax 336.578.5554	800.334.4270
<b>Berlin, NJ</b>	Tel 856.768.2275	Fax 856.768.2385	800.225.0215
<b>Ajax, ON</b>	Tel 905.686.5200	Fax 905.686.8349	

THE  
**NOVAFLEX**<sup>®</sup>  
GROUP 

Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)