

## R-2



Size Range (In) ..... 1.25" to 18"  
 ..... custom to 24"  
 Standard Length (Ft) ..... 25', 50'  
 ..... 14" and above in 25' only  
 Standard Colors ..... blue, clear  
 Temperature Range (°F) ..... 20° to 160°

**A** **F** **RU** Ship

- Light weight PVC hose reinforced with a spring steel wire helix
- Great flexibility with tight bending characteristics
- Good chemical and moisture resistance
- Good compressibility
- Excellent choice for ventilation applications, dust and fume removal
- Blue is listed as UL 94V-0 flame retardant
- Clear is manufactured with FDA acceptable materials
- Wall Thickness = .020"
- Available in metric sizes, consult sales team on pricing and minimums
- Available in an insulation vacuuming version (E-2)



## R-3



Size Range (In) ..... 1.25" to 12"  
 ..... custom to 24"  
 Standard Length (Ft) ..... 25', 50'  
 ..... 14" and above in 25' only  
 Standard Colors ..... blue, clear  
 Temperature Range (°F) ..... 20° to 160°

**M** **RU** Ship

- Heavy weight PVC hose reinforced with a coated spring steel wire helix (sizes 14" I.D. and above not available with a coated wire)
- Excellent internal and external abrasion resistance
- Good chemical and moisture resistance
- Excellent choice for ventilation applications, dust and fume removal
- Blue is listed as UL 94V-0 flame retardant
- Clear is manufactured with FDA acceptable materials
- Wall Thickness = .045"
- Available in metric sizes, consult sales team on pricing and minimums



## R-4




Size Range (In) ..... 2" to 12"  
 Standard Length (Ft) ..... 10', 25', 50'  
 Standard Color ..... clear  
 Temperature Range (°F) ..... 20° to 160°

**D** **M**

- Medium weight PVC hose reinforced with a spring steel wire helix
- Good for positive pressure applications
- Great compressibility
- Construction allows for value packaging by reducing the box size, reducing warehouse space and shipping costs
- Ideal for dust and woodworking applications
- Good chemical and moisture resistance
- Manufactured with FDA acceptable materials
- Available in a stretch version (R-4 Stretch)
- Wall Thickness = .028"



## ADC



Size range (In) ..... 6" to 12"  
 ..... custom to 18"  
 Standard Length (Ft) ..... 25'  
 Standard Color ..... clear  
 Temperature Range (°F) ..... 20° to 160°

**A** **F**

- Very light weight PVC hose reinforced with a spring steel wire helix
- Good for positive pressure applications
- Great compressibility
- Excellent flexibility with tight bending characteristics
- Good chemical and moisture resistance
- Manufactured with FDA acceptable materials
- Wall Thickness = .015"

