



Suction hose and pressure hose according to DIN EN 45545-2, medium-heavy duty

Application

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- rail vehicle (DIN 5510, DIN EN 45545-2), train, railway, tram, boat, ship/ vessel, yacht: ventilation, heating, roof drainage, sand conveying in rail vehicle braking systems, sanitary installation

Properties

- medium-heavy duty
- highly abrasion resistant
- insulating
- microbe and hydrolysis resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- flame-retardant according to: DIN EN 45545-2; R1 HL1, HL2, HL3; R22 HL1, HL2; R23 HL1, HL2
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- 40°F to 195°F

Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall
- wall: special premium polyurethane with flame retardant additive (Pre-PUR®)
- wall thickness 0.035 in approx.
- special thermal insulation layer

Delivery variants

- further diameters and lengths available on request

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Production lengths	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	
- / 20	1.122	36.695	14.322	1.339	0.141	5	352-0020-5400
- / 22	1.201	33.577	12.993	1.496	0.161	5	352-0022-5400
1 / 25	1.319	29.806	11.369	1.732	0.181	5	352-0025-5400
- / 30	1.555	25.164	8.416	2.047	0.228	5	352-0030-5400
1,25 / 32	1.634	23.642	7.825	2.205	0.249	5	352-0032-5400
1,5 / 38	1.870	20.088	6.644	2.520	0.282	5	352-0038-5400
- / 40	1.949	19.145	6.349	2.598	0.296	5	352-0040-5400
- / 42	2.028	18.130	0.591	2.677	0.316	5	352-0042-5400
1,75 / 44-45	2.146	17.042	5.611	2.795	0.336	5	352-0045-5400
2 / 50-51	2.343	15.447	5.020	3.150	0.356	5	352-0050-5400
- / 55	2.539	14.069	4.577	3.268	0.397	5	352-0055-5400
2,36 / 60	2.736	11.603	4.134	3.543	0.430	5	352-0060-5400
2,5 / 63-65	2.933	10.805	3.691	3.937	0.464	5	352-0063-5400
- / 70	3.169	10.008	2.510	4.094	0.511	5	352-0070-5400
3 / 75-76	3.406	9.355	2.362	4.291	0.551	5	352-0075-5400
- / 80	3.563	8.775	2.215	4.567	0.585	5	352-0080-5400
3,5 / 89-90	3.957	7.760	1.919	5.039	0.645	5	352-0090-5400
4 / 100-102	4.429	7.034	1.919	5.512	0.806	5	352-0100-5400
4,72 / 120	5.138	5.874	1.477	6.496	1.001	5	352-0120-5400
5 / 125-127	5.413	5.657	1.477	6.693	1.250	5	352-0125-5400
6 / 150-152	6.398	4.714	1.329	7.874	1.485	5	352-0150-5400
7 / 178-180	7.500	3.916	1.034	9.449	1.788	5	352-0180-5400

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

intended as a general guide only.

Accessories



CONNECT 270-271



CLAMP 208



CLAMP 212