CATALOG CH ADDENDUM

High Capacity Pump Hose & Assemblies



ABBOTTRUBBER COMPANY, INC.

LIST PRICE CATALOG - APRIL 2025

ABBOTT RUBBER COMPANY, INC.



We welcome you to visit our 112,000 square foot facility in Itasca IL.

Serving the Construction Market for Over 70 Years



Order Entry and Technical Assistance - Our Specialty



1311 Meacham Road Itasca, IL. 60143 (847) 952-1800 TOLL FREE (800) 852-1855 FAX (847) 952-0156 E-MAIL sales@abbottrubber.com ORDER ONLINE WWW.abbottrubber.com



Large Diameter Hose Crimp Capabilities

| | INDE | | |
|---|------|-------------------------------------|------|
| Item | Page | Item | Page |
| Clear Braid PVC Water Suction Hose | 3 | Extra Heavy Duty PVC Discharge Hose | 5 |
| Low-Temp Clear Braid PVC Water Suction Hose | 3 | Heavy Duty PVC Water Discharge Hose | 6 |
| Rubber Water Suction Hose | 4 | Rubber Water Discharge Hose | 6 |
| Flanged Heavy Duty Rubber Suction Hose | 4 | PVC Water Discharge Hose | 6 |
| Pumpflex Water Suction Hose | 5 | Couplings and Accesories | 7 |
| | | | |








🙆 ntinental 🏂









SUCTION AND DISCHARGE HOSE ClearBraidPVCWaterSuctionHose

---ClearBraidPVC WaterSuctionHose (Series 1242)

Service: PVC water suction hose specifically designed for applications where visual flow is desired. Lightweight and corrugated for flexibility.

Construction: Clear flexible PVC with an orange rigid PVC helix for abrasion resistance. Reinforced with a layer of spiral polyester for strength and handling pressure applications.

| I.D. | Weight Ft | Price/10 Ft w/ C&E Couplings | Price/20 Ft w/ C&E Couplings | Price/25 Ft w/ C&E Couplings |
|------|----------------|---------------------------------|---------------------------------|---------------------------------|
| 4" | 1.74 | \$416.00 | \$616.50 | \$701.50 |
| 6" | 3.88 | 934.00 | 1,392.00 | 1,620.50 |
| 8" | 5.54 | 1,861.50 | 2,655.00 | 3,052.00 |
| 10" | 8.68 | | | |
| 12" | 10.30 | | | |
| I.D. | Bend Radius | Price/10 Ft w/ Ball & Socket | Price/20 Ft w/ Ball & Socket | Price/25 Ft w/ Ball & Socket |
| 4" | 7.1 | \$707.50 | \$911.50 | \$1,013.50 |
| 6" | 10.2 | 1,590.00 | 2,047.50 | 2,276.50 |
| 8" | 15.7 | 2,460.50 | 3,254.50 | 3,651.00 |
| 10" | 24.8 | | 4,990.00 | 5,565.00 |
| 12" | 45.0 | | 7,242.50 | |
| | | | ALSO AVAIL | ABLE WITH NPT MALES |

Temperature Range: 15°F to 140°F.

-Low-TempClearBraidPVCWaterSuctionHose

Service: New low-temperature version of our standard Clear Braid PVC Suction Hose. Lightweight and extremely flexible.

(Series 1242BL)

Construction: Clear flexible PVC compounded for use in low temperature applications. Blue rigid PVC helix for abrasion resistance. Reinforced with a layer of spiral polyester for strength and handling pressure applications.

Temperature Range: -40°F to 140°F.

| I.D. | Weight Ft | Price/10 Ft w/ C&E Couplings | Price/20 Ft w/ C&E Couplings | Price/25 Ft w/ C&E Couplings |
|------------|-----------------------------|--|--|--|
| 4" | 1.74 | \$412.00 | \$605.00 | \$754.00 |
| 6" | 3.88 | 900.50 | 1,324.50 | 1,497.50 |
| 8" | 5.54 | 1,803.50 | 2,539.00 | 2,907.00 |
| 10" | 8.68 | | | |
| 12" | 10.30 | | | |
| | | | | |
| I.D. | Bend Radius | Price/10 Ft w/ Ball & Socket | Price/20 Ft w/ Ball & Socket | Price/25 Ft w/ Ball & Socket |
| I.D. 4" | | | | |
| | Radius | w/ Ball & Socket | w/ Ball & Socket | w/ Ball & Socket |
| 4" | Radius 7.0 | w/ Ball & Socket \$690.00 | w/ Ball & Socket \$897.00 | w/ Ball & Socket \$1,000.50 |
| 4" 6" | Radius 7.0 9.0 | w/ Ball & Socket \$690.00 1,517.50 | w/ Ball & Socket \$897.00 1,941.50 | w/ Ball & Socket \$1,000.50 2,153.50 |



Kana flex



ALSO AVAILABLE WITH NPT MALES



🛃 www.abbottrubber.com

SUCTION AND DISCHARGE HOSE -Rubber Water Suction

Service: Heavy duty flexible rubber hose designed for water suction and discharge applications.

Construction: Black smooth EPDM blend tube reinforced with multiple plies of polyester fabric and a steel wire helix for suction service. Black rubber cover with yellow stripe.

Temperature Range: -10°F to 180°F.

| I.D. | Weight Ft | Price/10 Ft w/ C&E Couplings | Price/20 Ft w/ C&E Couplings | Price/25 Ft w/ C&E Couplings |
|------|----------------|---------------------------------|---------------------------------|---------------------------------|
| 4" | 2.79 | \$428.00 | \$664.50 | \$782.50 |
| 6" | 5.75 | 866.50 | 1,295.50 | 1,510.00 |
| 8" | 6.59 | 1,924.50 | 2,753.00 | 3,250.00 |
| 10" | 10.25 | | | |
| 12" | 13.50 | | | |
| I.D. | Bend Radius | Price/10 Ft w/ Ball & Socket | Price/20 Ft w/ Ball & Socket | Price/25 Ft w/ Ball & Socket |
| 4" | 18.0 | \$719.50 | \$956.00 | \$1,074.50 |
| 6" | 31.0 | 1,522.50 | 1,951.50 | 2,166.00 |
| 8" | 42.0 | 2,436.00 | 3,264.50 | 3,678.50 |
| 10" | 50.0 | 3,678.00 | 5,178.00 | |
| 12" | 60.0 | 5,204.50 | 6,898.00 | |
| | | | | |

ALSO AVAILABLE WITH NPT MALES

Flanged Heavy Duty Rubber Water Suction Hoses

(Series 1216)

(Series 1210)

Service: Heavy duty water suction hose designed for use with high capacity pumps for positive or negative pressures to full vacuum and for dock service.

Construction: Black oil resistant tube reinforced with fabric plies and helical steel wire. Black Neoprene cover. Includes built-in 150# fixed x floating ANSI flanges.

Temperature Range: -40°F to 190°F.

| I.D. | Length | W/P @70°F | Bend Radius | Weight Lbs. Ea | Price/Ea |
|------|--------|--------------|-------------|-------------------|------------|
| 4" | 20' | 250# | 24.0 | 115 | \$1,795.00 |
| 6" | 20' | 250# | 32.0 | 190 | 3226.00 |
| 8" | 20' | 250# | 40.0 | 305 | 4815.00 |
| 10" | 20' | 250# | 60.0 | 450 | 6952.00 |
| 12" | 20' | 250# | 70.5 | 550 | 8820.50 |



SUCTION AND DISCHARGE HOSE PumpflexTM Water Suction (Series 1218)

Service: New extremely flexible suction and discharge hose. Will handle oily water. Lightweight and easy to handle. Use for full suction and pressures to 150 PSI.

Construction: Multi-layer coated fabric with helical wire support. Purple with a white stripe.

Temperature Range: -40°F to 200°F.

| I.D. | Weight Ft | Price/10 Ft w/ Nipple x Nipple | Price/20 Ft w/ Nipple x Nipple |
|----------------|---------------------------------------|--|--|
| 4" | 2.70 | On Application | On Application |
| 6" | 5.50 | On Application | On Application |
| 8" | 8.00 | On Application | On Application |
| 10" | 14.50 | On Application | On Application |
| 12" | 18.50 | On Application | On Application |
| | | | |
| I.D. | Bend Radius | Price/10 Ft w/ Flange x Flange | Price/20 Ft w/ Flange x Flange |
| I.D. 4" | | | |
| | Radius | w/ Flange x Flange | w/ Flange x Flange |
| 4" | Radius 14.2 | w/ Flange x Flange \$1,627.50 | w/ Flange x Flange \$2,154.50 |
| 4" 6" | Radius 14.2 22.0 | w/ Flange x Flange \$1,627.50 2,663.50 | w/ Flange x Flange \$2,154.50 3,162.00 |
| 4" 6" 8" | Radius 14.2 22.0 30.0 | w/ Flange x Flange \$1,627.50 2,663.50 3,565.00 | w/ Flange x Flange \$2,154.50 3,162.00 4,805.00 |



-ExtraHeavyDutyPVCDischargeHose~

(Series 1166/1167)

GOOD YEAR.

BAUER


Service: Heavy weight lay-flat hose designed for open end discharge using high capacity pumps. Will handle oily water.


Construction: Black oil resistant PVC/Nitrile tube and cover reinforced with extra heavy fabric. Also available in yellow through 6 in. 3:1 Design Factor

Temperature Range: -20°F to 200°F.

| I.D. | WP @70°F | Weight Ft | Price/50 Ft w/ Ball & Socket | Price/100 Ft w/ Ball & Socket |
|------|-------------|--------------|---------------------------------|----------------------------------|
| 4" | 200# | 0.83 | \$1,119.50 | \$1,791.50 |
| 6" | 150# | 1.60 | 2,044.50 | 3,080.50 |
| 8" | 150# | 2.30 | 3,481.00 | 5,455.00 |
| 10" | 125# | 3.20 | 3,099.00 | 5,655.50 |
| 12" | 125# | 3.50 | 6,685.50 | |







SUCTION AND DISCHARGE HOSE

-HeavyDutyPVCWaterDischargeHose、

(Series 1152) Service: Heavy duty PVC lay-flat hose designed for open end water discharge applications. Rolls up for easy storage Construction: Red PVC tube and cover reinforced with three plies of spiral polyester. Temperature Range: -5°F to 150°F. WP Price/100 Ft Weight Price/50 Ft w/ Ball & Socket I.D. @70°F w/ Ball & Socket Ft GOODFYEAR 4" 150# 0.85 \$793.50 \$1,139.50 6" 150# 1.20 1,608.50 2,208.50 8" 70# 2,320.00 1.30 3,133.00 **GOOD**[®]YEAR BAUER

-RubberWaterDischargeHose

Service: Rubber hose for water discharge applications:

Construction: Non-wire construction. Black smooth rubber tube reinforced with 4 ply equivalent of woven polyester fabric. Black abrasion and weather resistant SBR cover with yellow stripe.

Temperature Range: -10°F to 150°F.

| I.D. | WP @70°F | Weight Ft | Price/Ft |
|------|-------------|--------------|----------|
| 4" | 150# | 1.85 | \$22.88 |
| 6" | 125# | 3.90 | 44.64 |
| 8" | 100# | 5.25 | 73.22 |
| 10" | 100# | 6.29 | 91.54 |
| 12" | 100# | 7.83 | 121.28 |



(Series 1120)

(Series 1148)

-PVCWaterDischargeHose

Service: Designed for moderate open end water discharge service. Lightweight and coils easily.

Construction: Lay flat close woven nylon jacket impregnated with a blue PVC tube and cover.

Temperature Range: -5°F to 150°F.

| I.D. | W/P @70°F | Maximum Length | Price/Ft |
|------|--------------|-------------------|----------|
| 4" | 70# | 300' | \$3.34 |
| 6" | 60# | 300' | 6.24 |
| 8" | 35# | 300' | 14.00 |
| 10" | 35# | 100' | 34.50 |
| 12" | 35# | 100' | 45.00 |
| 14" | 30# | 100' | 102.00 |
| 16" | 30# | 100' | 118.50 |
| | | | |



6



COUPLINGS & ACCESORIES









PROUD ASSOCIATE MEMBER OF







1311 MEACHAM RD. • ITASCA, IL 60143 • 800.852.1855 E-MAIL sales@abbottrubber.com • WEBSITE www.abbottrubber.com

ISO 9001:2015 Certified

