

ABBOTT RUBBER COMPANY, INC.

1311 Meacham Rd. Itasca, IL 60143 (847) 952-1800 (800) 852-1855 FAX (847) 952-0156

Bolted Polypropylene Ball Valves



Features

- Stainless Steel Bolts
- Precision molded in polypropylene.
- Polypropylene is reinforced with fiberglass for additional strength. Self-aligning ball moves freely against the Teflon® seats for smooth operation. The valve opens and closes with little pressure on the handle.
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats.
- Viton "O" rings
- Teflon® self-lubricating stem bushings and seats cannot stick or bind.

Vendor



| Part # | I.D. | Braid | W/P @ 70° |
|-----------|---------------------------------------|---------------|-----------|
| V050FP | 1/2" Female NPT x 1/2" Female NPT | 1/2" | 150 |
| V075FP | 3/4" Female NPT x 3/4" Female NPT | 3/4" | 150 |
| V100 | 1" Female NPT x 1" Female NPT | Standard Port | 150 |
| V100FP | 1" Female NPT x 1" Female NPT | 1" | 150 |
| V125 | 1 1/4" Female NPT x 1 1/4" Female NPT | Standard Port | 150 |
| V125FP | 1 1/4" Female NPT x 1 1/4" Female NPT | 1 1/4" | 150 |
| V150FP | 1 1/2" Female NPT x 1 1/2" Female NPT | 1 1/2" | 150 |
| V200 | 2" Female NPT x 2" Female NPT | 1 1/2" | 150 |
| V204FP | 2" Female NPT x 2" Female NPT | 2" | 100 |
| V200FP | 2" Female NPT x 2" Female NPT | 2" | 100 |
| V300 | 3" Female NPT x 3" Female NPT | 2 1/2" | 100 |
| V300FP | 3" Female NPT x 3" Female NPT | 2" | 100 |
| V400FP | 4" Female NPT x 4" Female NPT | 4" | 100 |
| V204FP | 2" Female NPT x 2" Male Adapter | 2" | 100 |
| VFMT204FP | 2" Male NPT x 2" Male Adapter | 2" | 100 |
| VMT204FP | 2" Female NPT x 2" Male NPT | 2" | 100 |
| VMM204FP | 2" Male NPT x 2" Male NPT | 2" | 100 |