



## T204AA 75 PSI SBR Water S & D Hose

**Applications:**

Suction and discharge of water for irrigation and construction.

**Cover:**

Black SBR – ozone and abrasion-resistant.

**Reinforcement:**

Spiraled high tensile textile cords with flexible steel helix wire.

**Tube:**

Black SBR.

**Working Pressure:**

Constant Pressure – 5 Bar (75 PSI)

**Temperature Range:**

-22°F (-30°C) to 176°F (+80°C)

**Branding:**

ALFAGOMMA– ITALY – T204 (embossed)

**Standard Length:**

20, 25, 50, 100 feet: 6"  
20, 25, feet: 8"

### Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Vacuum HG (in.)	Min. Bending Radius (in. @ 68°F)	Weight (lbs./ft.)
T204AA600	6	152	6.54	166	75	24	30	4.13
T204AA800	8	203	8.70	221	75	21	40	7.06

**COUPLING SUGGESTIONS**

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.