

Water Discharge



T253AA 150 PSI EPDM Layflat Water Discharge Hose

FOR APPLICATIONS INVOLVING
INDUSTRIAL ACID CHEMICALS AND
ALCOHOLS, PLEASE REFER TO T505OG
AND T509OE CHEMICAL HOSES



Applications:

High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation.

Cover:

Black EPDM – abrasion and ozone-resistant.

Reinforcement:

High tensile textile cords.

Tube:

Black EPDM.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY – T253 10 BAR (150 PSI) EPDM
WATER DISCHARGE (in green letters)

Standard Length:

100 feet: 1 1/2" through 10"
50 feet: 6", 6 5/8", 8", 10" & 12"

* 6⁵/₈" referred to as Elephant Trunk Hose – Ideal for "Irrigation Boots."

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T253AA150	1 1/2	38	1.81	46	150	0.37
T253AA200	2	51	2.32	59	150	0.50
T253AA250	2 1/2	63	2.80	71	150	0.60
T253AA300	3	76	3.31	84	150	0.86
T253AA400	4	102	4.33	110	150	1.19
T253AA600	6	152	6.38	162	150	2.00
T253AA662	6 5/8	168	7.01	178	150	2.17
T253AA800	8	203	8.46	215	150	2.82
T253AA1000	10	254	10.63	270	150	5.11
T253AA1200	12	305	12.56	319	150	5.93

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.