



Sweeper hose, heavy duty, exterior folds, very flexible

Application

- municipal vehicle: sweeper, sweeping machine

Properties

- heavy duty
- highly flexible + compressible
- highly abrasion resistant
- protected, flow-optimizing exterior folds
- microbe resistant

- very good low temperature flexibility
- according to DIN 26057 Type 3
- REACH according to --> Technology / Technical Information / REACH
- conforms to RoHS guideline

Temperature range

- -40 °F to 195 °F

Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0.055 to 0.06 in approx.

Delivery variants

- further diameters and lengths available on request
- transparent + partially black colored (standard)
- special colors: transparent, partially colored, completely colored
- customer-specific branding

I.D. (in / mm)	outer Ø (in)	Pressure (psi)	Vacuum (inHG)	Bending radius (in)	Weight (lb/ft)	Dimensions in Stock (ft)	Production lengths (ft)	Order No.
partially black colored								
5,5 / 140	6.024	5.947	6.792	7.874	1.297	-	5 10	355-0140-5200
6,3 / 160	6.811	5.729	5.758	7.874	1.613	-	5 10	355-0160-5200
- / 170	7.205	5.657	5.315	9.055	1.714	-	5 10	355-0170-5200
7 / 178-180	7.598	5.584	4.872	10.236	1.815	-	5 10	355-0180-5200
- / 195	8.189	5.439	4.134	16.378	1.949	-	5 10	355-0195-5200
- / 200	8.465	5.366	3.839	16.378	2.016	-	5 10	355-0200-5200
8 / 203	8.504	5.323	3.691	12.992	2.124	5	10	355-0203-5200
- / 206	8.622	5.294	3.544	13.189	2.157	-	5 10	355-0206-5200
- / 208	8.701	5.221	3.396	13.307	2.184	-	5 10	355-0208-5200
- / 225	9.370	4.859	2.953	14.331	2.352	-	5 10	355-0225-5200
9 / 228-229	9.488	4.641	2.953	14.488	2.386	-	5 10	355-0228-5200
- / 250	10.354	4.061	2.805	15.787	2.601	-	5 10	355-0250-5200
10 / 254	10.512	4.134	2.362	16.024	2.641	5	10	355-0254-5200
- / 257	10.630	4.206	2.215	16.220	2.675	-	5 10	355-0257-5200
- / 275	11.339	3.916	2.067	17.283	2.856	-	5 10	355-0275-5200
11 / 280	11.535	3.844	2.067	17.559	2.910	-	5 10	355-0280-5200
- / 300	12.323	3.626	1.919	18.701	3.192	-	5 10	355-0300-5200
12 / 305	12.520	3.553	1.772	18.976	3.259	5	10	355-0305-5200
- / 400	16.260	2.611	1.181	24.252	4.603	-	5 10	355-0400-5200
16 / 405-406	16.496	2.538	1.329	24.646	4.691	-	5 10	355-0406-5200
transparent								
5,5 / 140	6.024	5.947	6.792	7.874	1.297	-	5 10	355-0140-5205
6,3 / 160	6.811	5.729	5.758	7.874	1.613	-	5 10	355-0160-5205
- / 170	7.205	5.657	5.315	9.055	1.714	-	5 10	355-0170-5205
7 / 178-180	7.598	5.584	4.872	10.236	1.815	-	5 10	355-0180-5205

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
- / 195	8.189	5.439	4.134	16.378	1.949	-	5 10	355-0195-5205
- / 200	8.465	5.366	3.839	16.378	2.016	-	5 10	355-0200-5205
8 / 203	8.504	5.323	3.691	12.992	2.124	-	5 10	355-0203-5205
- / 206	8.622	5.294	3.544	13.189	2.157	-	5 10	355-0206-5205
- / 208	8.701	5.221	3.396	13.307	2.184	-	5 10	355-0208-5205
- / 225	9.370	4.859	2.953	14.331	2.352	-	5 10	355-0225-5205
9 / 228-229	9.488	4.641	2.953	14.488	2.386	-	5 10	355-0228-5205
- / 250	10.354	4.061	2.805	15.787	2.601	-	5 10	355-0250-5205
10 / 254	10.512	4.134	2.362	16.024	2.641	-	5 10	355-0254-5205
- / 257	10.630	4.206	2.215	16.220	2.675	-	5 10	355-0257-5205
- / 275	11.339	3.916	2.067	17.283	2.856	-	5 10	355-0275-5205
11 / 280	11.535	3.844	2.067	17.559	2.910	-	5 10	355-0280-5205
- / 300	12.323	3.626	1.919	18.701	3.192	-	5 10	355-0300-5205
12 / 305	12.520	3.553	1.772	18.976	3.259	-	5 10	355-0305-5205
- / 400	16.260	2.611	1.181	24.252	4.603	-	5 10	355-0400-5205
16 / 405-406	16.496	2.538	1.329	24.646	4.691	-	5 10	355-0406-5205

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

Accessories



CONNECT 240 + 241 AS



CLAMP 211



CONNECT 270-271