



Sweeper hose, heavy duty and reinforced, interior folds

Application

- municipal vehicle: sweeper, sweeping machine

Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- very good low temperature flexibility
- REACH according to --> Technology / Technical Information / REACH

- REACH according to --> Technology / Technical Information / REACH
- conforms to RoHS guideline

Temperature range

- -40°F to 195°F

Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)

- wall thickness 0.06 to 0.07 in approx.
- reinforcement of the primary abrasion areas

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: transparent, partially colored, completely colored
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Order No.	Production lengths
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)		(ft)
8 / 200-203	8.465	5.294	3.691	7.008	1.781	5	355-0203-5015	-
- / 208	8.661	5.221	3.544	7.165	1.841	5	355-0208-5015	12 25
10 / 254	10.472	4.279	2.215	8.622	2.392	5	355-0254-5016	-
12 / 305	12.598	3.699	1.772	10.315	3.427	5	355-0305-5015	-

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

Accessories



CONNECT 270-271



CONNECT 240 + 241 AS



CLAMP 211