

Quick Connect Hose Barb

Part Number: HS2KRFP03A

Patent Pending



Titanium and Stainless steel cam arms lock hose in place for secure connection



1/4" replaceable EPDM or Viton gasket provides a leak-proof seal

Enhance operations by incorporating Salco's quick connect hose barb into your transfer process.

- Stainless steel reinforced for increased durability.
- Produced from UHMW-PE for resistance in corrosive/abrasive environments.
- Lightweight, easy to attach and detach.
- 125psi pressure rating allows for the unloading of a tank truck or railcar.
- Can be used in service temperatures ranging from -30°F to 150°F.
- Currently available in 2".

Compatibility Chart

UHMWPE

	70° F	122° F	170° F
Caustic Soda	1	1	1
Ferric Nitrate	1	*	*
Ferric Sulfate	1	*	*
Ferrous Chloride	1	*	*
Ferrous Sulfate	1	*	*
Hydrochloric Acid (>20%)	1	1	Boiling NR
Hydrochloric Acid (50%)	1	1	Boiling NR
Hydrochloric Acid (>40%)	1	2	*
Hydrofluosilicic Acid	1	*	*
Hydrofluorasilicic Acid	1	*	*
Hypochlorous Acid	*	*	*
Sulfuric Acid (10%)	1	1	*
Sulfuric Acid (30%)	1	1	*
Sulfuric Acid (60%)	1	1	*
Sulfuric Acid (80%)	1	3	*
Sulfuric Acid (100%)	1	NR	*

- 1** <15% loss in property values. Little or no chemical attack.
- 2** 15-30% loss in property values. Minor chemical attack.
- 3** 30-50% loss in property values. Moderate chemical attack.
- NR** Not recommended. > 50% loss in property values.
- *** No data available.