

**Kuriyama of America, Inc.**

150 N MARTINGALE ROAD

SCHAUMBURG, IL 60173-5335 USA

Phone: (847) 755-0360**Toll-Free FAX:** (800) 800-0320**International FAX:** (847) 885-0996 **Email:** sales@kuriyama.com**Series HSC2846 Blue Polyurethane Self-Store Tubing & Reinforced Hose**

Ether based polyurethane self-store coiled tubing & hose assemblies for air tool service.

- Standard assemblies have 4" pigtail and 20" whip end.
- Permanent crimped male swivel brass fittings provide greater strength and pull-out resistance . . . rubber bend restrictors over fittings prevents scratches and scuffs.

**1**

<u>Item #</u>	<u>Size Code x Length</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 70°F (20°C)</u>	<u>Maximum Working Pressure at 122°F (50°C)</u>	<u>Working Length</u>	<u>Coil O.D.</u>	<u>Standard Package</u>	<u>Approx. Wt. per Pkg.</u>
<u>HSC2846-04X10</u>	04 x 10	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	8 ft	2 in	10	5 lb
<u>HSC2846-04X15</u>	04 x 15	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	12 ft	2 in	10	6.5 lb
<u>HSC2846-04X20</u>	04 x 20	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	16 ft	2 in	10	8.5 lb

<u>Item #</u>	<u>Size Code x Length</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 70°F (20°C)</u>	<u>Maximum Working Pressure at 122°F (50°C)</u>	<u>Working Length</u>	<u>Coil O.D.</u>	<u>Standard Package</u>	<u>Approx. Wt. per Pkg.</u>
<u>HSC2846-04X25</u>	04 x 25	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	20 ft	2 in	10	10 lb
<u>HSC2846-04X30</u>	04 x 30	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	24 ft	2 in	10	12 lb
<u>HSC2846-04X50</u>	04 x 50	1/4 in 6.5 mm	0.375 in 9.5 mm	125 psi	75 psi	40 ft	2 in	1	2.0 lb
<u>HSC2846-06X10</u>	06 x 10	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	8 ft	3 in	5	5 lb
<u>HSC2846-06X15</u>	06 x 15	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	12 ft	3 in	5	7.0 lb
<u>HSC2846-06X20</u>	06 x 20	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	16 ft	3 in	5	9.00 lb
<u>HSC2846-06X25</u>	06 x 25	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	20 ft	3 in	5	11 lb
<u>HSC2846-06X30</u>	06 x 30	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	24 ft	3 in	5	12 lb
<u>HSC2846-06X50</u>	06 x 50	3/8 in 9.5 mm	0.570 in 14.5 mm	125 psi	75 psi	40 ft	3 in	1	4.0 lb