

MANTEX HP



Mandals Mantex HP is a lay-flat hose made for compressed air to withstand higher than usual working pressures, while still offering a light weight solution with its ease of deployment and storage.

INDUSTRIES

COMPRESSED AIR

DESIGN

- Thermoplastic polyester based polyurethane (TPU)

FEATURES

- Lighting, yet rugged and hard wearing hose.
- The low weight combined with a high pressure rating makes the hose popular and easy to use.
- The hose does not stretch when pulled and has a very high pressure rating versus wall thickness.
- Excellent abrasion resistance.
- Temperature reach - 30° to 110° C.

ADVANTAGE

- Field proven hose with a long track record.
- Lengths up to 40 meters.

TECHNICAL DATA

INNER DIAMETER		WALL THICKNESS		WEIGHT		BURST PRESSURE		TENSILE STRENGTH	
Inch	mm	Inch	mm	Lbs / ft	Kg / m	Psi	Bar	X1000 kbs	Tons
2	51,0 + 2,0	0,17	4,4	0,55	0,82	2535	175	31,7	14,3
3	76,0 + 2,0	0,18	4,5	1,2	0,80	1300	103	46,6	21



Contact
sales@mandals.com
 (47) 38 27 24 00
 Nordre Banegate 26, 4515Mandal, Norway