

Concrete, Plaster & Grout



EHK007

Marauder Heavy Duty



Application

- For high pressure concrete pumping and placing, used in the end of concrete pump boom
- Heavy duty construction for applications needing long lasting durability

Markets

- Construction
- Cement placement
- Boom truck

Construction

Tube Abrasion resistant anti-static natural rubber and CBR rubber blend

Reinforcement

High tensile steel cords

Cover Abrasion, ozone and weather resistant pin-pricked special synthetic rubber

Color Black

Certifications

Meets the requirements of ASME B30.27-2014

Abrasion loss value acc. DIN53516 $\leq 60\text{mm}^3$

Operating temperature

-40°C to +70°C
(-40°F to +158°F)

Packaging

100 ft

Order Fulfillment

Made to Stock
Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHK007-32-100	50.8	2.00	70.0	2.76	86.0	1250	200	2900	200	7.87	3.03	2.04	30.5	100
EHK007-40-100	63.5	2.50	88.0	3.46	86.0	1250	200	2900	240	9.45	4.48	3.01	30.5	100
EHK007-48-100	76.2	3.00	102.0	4.02	86.0	1250	200	2900	275	10.83	5.46	3.67	30.5	100
EHK007-64-100	101.6	4.00	130.0	5.12	86.0	1250	200	2900	350	13.78	8.46	5.68	30.5	100
EHK007-80-100	127.0	5.00	155.0	6.10	86.0	1250	200	2900	425	16.73	9.63	6.47	30.5	100

Type of couplings

- Victaulic male NPT

Contact coupling manufacturer for attachment procedure and other coupling recommendations