



PVC hose

Application

- flexible hose/ ducting for liquids and for gases
- hose/ tubing pump
- industrial washing machine: washing water hose
- compressed air hose, cooling water hose, water hose
- heating hose: interior hose for media transfer

Properties

- highly flexible

- crush resistant
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5 °F to 140 °F

Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: full colored
- customer-specific branding

I.D.	outer Ø	Wall thickness	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(in)	(lb/ft)	(ft)	
- / 2	0.157	0.039	0.007	100	400-9020-0000
1/8 / 3	0.197	0.039	0.013	100	400-9030-0000
- / 4	0.236	0.039	0.013	100	400-9040-0000
- / 4	0.276	0.059	0.020	100	400-9040-2182
- / 5	0.315	0.059	0.027	100	400-9050-0000
1/4 / 6	0.354	0.059	0.034	100	400-9060-0000
1/4 / 6	0.394	0.079	0.047	100	400-9060-2184
- / 7	0.394	0.059	0.034	100	400-9070-0000
5/16 / 8	0.472	0.079	0.054	50	400-9080-0000
- / 9	0.512	0.079	0.060	50	400-9090-0000
3/8 / 10	0.551	0.079	0.067	50	400-9100-0000
- / 12	0.669	0.098	0.101	50	400-9120-0000
- / 14	0.748	0.098	0.114	50	400-9140-0000
- / 15	0.787	0.098	0.121	50	400-9150-0000
5/8 / 16	0.866	0.118	0.155	50	400-9160-0000
- / 18	0.945	0.118	0.175	50	400-9180-0000
- / 20	0.945	0.079	0.121	50	400-9200-0000
- / 20	1.024	0.118	0.188	50	400-9200-2175
7/8 / 22	1.102	0.118	0.208	50	400-9220-0000
1 / 25	1.220	0.118	0.228	25	400-9250-0000
1 1/8 / 30	1.457	0.138	0.323	25	400-9300-0000
1 1/4 / 32	1.575	0.157	0.397	25	400-9320-0000
1 1/2 / 38	1.890	0.197	0.591	25	400-9380-0000
- / 40	1.890	0.157	0.484	25	400-9400-0000
- / 40	1.969	0.197	0.618	25	400-9400-2187
- / 50	2.362	0.197	0.753	25	400-9500-0000
2 3/8 / 60	2.756	0.197	0.894	25	400-9600-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

Accessories



CLAMP 208