

Specialty

H1941

Nyall

**Application**

- Spraying pesticides and fertilizers
- Paint spray

Markets

- Agriculture

Construction**Tube** Nylon**Reinforcement**

1-fiber braid

Cover Red - Vinyl Nitrile,
Black - Neoprene
RMA Class B oil resistant

Color Red (RD), Black (BK)

Certification

RMA Class B cover
Red - MSHA IC-84/72
Black - MSHA IC-46/6

Operating temperature

-34°C to +71°C
(-30°F to +160°F)

Packaging

500 ft

Order Fulfillment

Made to Stock

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
H194104RD-500R	6.4	0.25	13.4	0.53	35.0	500	140.0	2000	0.12	0.08	152.4	500
H194106RD-500R	9.7	0.38	18.3	0.72	35.0	500	140.0	2000	0.22	0.15	152.4	500
H194108RD-500R	12.7	0.50	20.6	0.81	35.0	500	140.0	2000	0.22	0.15	152.4	500

Type of coupling

- Danfoss "Z" series
- Danfoss TTC series
- Danfoss 4T series
- Danfoss E series
- Barb inserts

Contact coupling manufacturer for other coupling recommendations including proper metal selection (stainless, aluminum, brass etc.) and attachment procedure with crimp specifications.