

# Pacer™



## Product Specifications

### Application

Pacer™ is for all types of gasoline dispensing applications where flexibility and a lightweight hose is desired. Pacer™ is designed with a spiral textile reinforcement. This hose is UL 330 and CUL approved. Compatible with fuels up to E10 and B5.

### Construction

#### > Tube

Nitrile synthetic rubber (ORS)

#### > Cover

Chemivac synthetic rubber (ORS)

#### > Reinforcement

Spiral synthetic yarn with static wire

### Temperature Range

-40°F to 140°F (-40°C to 60°C)

### Packaging

Reels or coupled lengths

### Branding

Example: 3/4" Pacer™ Continental ContiTech

### Couplings

Available as factory-coupled assemblies only.

### Order Codes

595-017

## Pacer™

ID		Nom. OD		Weight	
in.	mm	in.	mm	lb./ft.	kg/m
5/8	15.9	0.98	24.9	0.28	0.42
3/4	19.1	1.15	29.2	0.37	0.55
1	25.4	1.50	38.1	0.60	0.89

### Air & Multipurpose

General Purpose  
Heavy Duty  
Push-on

### Chemical Transfer

### Cleaning Equipment

### Food

Dry Transfer  
Liquid Transfer  
Washdown

### Marine

### Material Handling

Abrasives  
Bulk Transfer  
Cement & Concrete

### Mining

### Petroleum

Aircraft Fueling  
Dispensing  
Dock  
Rig Supply  
Transfer Discharge  
Transfer S&D

### Specialty

### Steam

### Vacuum

### Water

Discharge  
Suction & Discharge  
Washdown  
Garden

### Welding

### Coupling Systems

### Equipment

### Appendix