

TPE hose, light weight, antistatic

## Application

- flexible hose/ ducting for hot and cold gases and for dust, powder, fibers
- granulate/ plastic dryer, hot air dryer
- film blowing machine, cooling air at the extrusion tool
- air supply: UV dryer, IR dryer
- textile industry, steam soaking: steam iron, industrial ironing machine, smoothing iron
- bus, utility vehicle, caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel/ marine, yacht: ventilation, heating
- heating system/ heater: fresh air supply

## Properties

- light weight
- highly flexible + compressible

- highly flexible + compressible
- very good heat resistance
- good resistance to oil, gasoline, and chemicals
- good resistance to alkalis and acids
- permanently antistatic wall: in accordance with ISO 8031 electrical and surface resistance  $<10^9 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- 40 °F to 255 °F
- short time to 300 °F

## Design

- PROTAPE® tape hose
- spring steel wire integrated in wall
- hose wall: thermoplastic rubber (TPE), antistatic
- wall thickness 0.015 in approx.

## Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colors: full colored
- customer-specific branding
- ID 1,5"/ 38mm 12/305mm compressed packed in poly bag (low transportation cost / risk, minimum storage size), ID 12"/315mm 20"/500mm not compressed

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	
2 / 50-51	2.283	3.408	3.101	1.299	0.155	10	320-0050-0000
2,36 / 60	2.677	2.828	2.658	1.496	0.175	10	320-0060-0000
- / 70	3.071	2.466	2.215	1.693	0.202	10	320-0070-0000
3 / 75-76	3.268	2.321	2.067	1.811	0.222	10	320-0075-0000
- / 80	3.465	2.176	1.919	1.890	0.242	10	320-0080-0000
4 / 100-102	4.291	1.740	1.624	2.283	0.349	10	320-0100-0000
5 / 125-127	5.276	1.378	1.329	2.795	0.430	10	320-0125-0000
5,5 / 140	5.827	1.233	1.181	3.071	0.477	10	320-0140-0000
6 / 150-152	6.260	1.160	0.738	3.268	0.511	10	320-0150-0000
6,3 / 160	6.614	1.088	0.738	3.465	0.538	10	320-0160-0000
7 / 178-180	7.402	0.943	0.591	3.858	0.612	10	320-0180-0000
8 / 200-203	8.268	0.870	0.591	4.252	0.679	10	320-0200-0000
- / 250	10.157	0.725	0.443	5.236	0.813	10	320-0250-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at [www.norres.com/us/technology/](http://www.norres.com/us/technology/). NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

## Accessories

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at [www.norres.com/us/technology/](http://www.norres.com/us/technology/). NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.



CLAMP 213




CONNECT 223



CLAMP 217




CONNECT 270-271



CLAMP 210 BRIDGE  
CLAMP



CLAMP 212



CONNECT 228