

# Material Handling



## T757AA / T737AA

600 PSI Plaster &  
Concrete Hose  
(Series T737AA for 3" ID)



### Applications:

Designed for pumping plaster, grout, and wet cement to placement sites.

### Cover:

Black conductive SBR/NR – abrasion and ozone resistant.

### Reinforcement:

High tensile textile cords.

### Tube:

Black conductive NR – abrasion resistant.

### Working Pressure:

Constant Pressure – 40 Bar (600 PSI)

### Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

### Branding:

ALFAGOMMA – ITALY T757 – 40 BAR (600 PSI)  
PLASTER & CONCRETE (in white letters) and  
ALFAGOMMA – ITALY T737 – 40 BAR (600 PSI)  
PLASTER & CONCRETE (in white letters)

### Standard Length:

100 feet

### Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T757AA150	1 1/2	38	2.13	54	600	0.82
T757AA200	2	51	2.64	67	600	1.09
T737AA300	3	76	4.09	104	600	2.96

### COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.