Cleaning Service



H9610


Joey Washdown 1000

Application

• For washdown of food processing facilities and equipment

Markets

- Food processing
- Industry cleaning
- Construction
- Poultry



Construction Tube Nitrile Reinforcement

Reinforcement1-braid wireCoverNitrile

Colors Yellow (YW), Gray (GY)

Operating temperature -40°C to +82°C (-40°F to +180°F)

Packaging 350 ft

Order Fulfillment

Made to Stock

Number	Hose I.D.		Hose	Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft	
H961006YW-350R	9.5	0.38	18.3	0.72	70.0	1000	280	4000	0.35	0.24	106.7	350	
H961008YW-350R	12.7	0.50	21.3	0.88	70.0	1000	280	4000	0.48	0.32	106.7	350	
H961012YW-350R	19.0	0.75	30.2	1.19	70.0	1000	280	4000	0.77	0.52	106.7	350	

Type of couplings

• Danfoss "Z" Series (-06, -08)

- Danfoss TTC series
- Danfoss 4T series

Contact coupling manufacturer for attachment procedure and other coupling recommendations.